

Fire Alarm Bells

The innovative and robust KOBELL range of motor driven fire alarm bells offers excellent sonorous tone, high sound output and proven reliability with some models only drawing 11mA. The 150mm (6 inch) version features the revolutionary aluminium gong offering enhanced acoustics and greater sound output.

Improved design means easier and quicker installation.

The low profile design meets the aesthetic requirements of architects and specifiers.

Weatherproof versions are supplied with an aluminium installation box complete with gasket, screws and 20mm threaded entry.

All bells and sounders can be supplied with OEM labels.



Features

- Low current consumption - only 11mA
- Quickly and easily installed
- Excellent sonorous tone 95dBA at 1 metre
- Slim profile
- Fully suppressed and polarised
- Simple installation with multi-fixing base plate
- Purpose-made weatherproof range



Specification

Description	6" (150mm) Internal	6" (150mm) Weatherproof	8" (200mm) Weatherproof
Model No.	MBF-6EV	MBA 6	MBA 8
Rated Voltage $\pm 20\%$	24Vdc		
Rated Current $\pm 20\%$	11 mA	12 mA	25 mA
Starting Voltage	19.2 Vdc	16.0 Vdc	16.9 Vdc
Sound Output @24V	95dBA	95dBA	95dBA
Temperature Range	-10 to +50°C		
Humidity Range	45 - 85%		
Weight	410g	820g (with back box)	1620g (with back box)
Gong Colour	Red		
Gong Construction	Aluminium	Aluminium	Steel

Installation

